











	Gwintowniki	Narzynki	Wzorec zarysu gwintu	Pokrętka do gwintowników	Oprawki do narzynek	Pokrętka typu "T"	Wkrętak	Pierścień dystansowy
ZAWARTOŚĆ	DIN-352 HSS - M3+M12 DIN-352/2 HSS - M14+M24 DIN-2181/2 HSS - MF≥14x1,25	DIN-EN 22 568 HSS 800	MWGa	PBPc	PBGa		RWWe	
								
	M3, M4, M5, M6, M8, M10, M12, M14, M16, M18, M20, M22, M24, M8x1, M10x1, M12x1,25, M12x1,5, M14x1,25, M14x1,5, M16x1,5, M18x1,5, M20x1,5, M22x1,5, M24x1,5	M3 M4 M5 M6 M8 M10 M12 M14 M16 M18 M20 M22 M24 M8x1 M10x1 M12x1,25 M12x1,5 M14x1,25 M14x1,5 M16x1,5 M18x1,5 M20x1,5 M22x1,5 M24x1,5	0,4 + 6 mm	Nr 2 zm.: 2,5 + 9 mm Nr 3: 4,9 + 14 mm	Ø25 x 9 mm Ø38 x 14 mm Ø45 x 18 mm Ø55 x 22 mm	Nr 1 (M2 ÷ M5)	4 x 90 mm	38 x 2 45 x 2 55 x 3
WYMIARY	550 x 380 x 70 mm							
CIĘŻAR	12 kg							